



CSA Aluminum Flexible Conduit

Part Number	Trade Size	Inside Diameter Min (inches)	Outside Diameter Max (inches)	Bending Diameter (inches)	Weight (Kg/m)
CSAAF3/8	3/8"	0.375	0.510	3.5	0.088
CSAAF7/16	7/16"	0.437	0.675	4.5	0.105
CSAAF1/2	1/2"	0.625	0.920	6.0	0.245
CSAAF3/4	3/4"	0.812	1.105	8.0	0.313
CSAAF1	1"	1.000	1.380	10.0	0.481
CSAAF1-1/4	1-1/4"	1.250	1.630	12.5	0.578
CSAAF1-1/2	1-1/2"	1.500	1.950	15.0	0.660
CSAAF2	2"	2.000	2.450	20.0	0.876
CSAAF2-1/2	2-1/2"	2.500	3.060	25.0	1.180
CSAAF3	3"	3.000	3.560	30.0	1.265
CSAAF3-1/2	3-1/2"	3.500	4.060	35.0	1.465
CSAAF4	4"	4.000	4.560	40.0	1.693

All values are nominal and subject to correction.

Application: Allows electrical contractors to run hundreds of feet of conduit without installing connectors between sections of conduit or the need for frequent braces to support the weight.

Construction: Light weight, primary, tempered aluminum alloy provides maximum strength and flexibility. Superior resistance to corrosion, with a smooth interior for easy pull through. Built in flexibility provides easy installation. 1/2 weight of steel

Standards: CSA Approved
ROHS

1-877-611-5122