



NMLT Non-Metallic Liquid-Tight Conduit

Part Number	Internal Diameter		External Diameter		Lengths	Weight
	Min	Max	Min	Max		
	inches	inches	inches	inches	FT	lbs/100'
NML3/8-100	0.484	0.504	0.690	0.710	100	12.8
NML1/2-100	0.622	0.640	0.820	0.840	100	13.3
NML3/4-100	0.820	0.840	1.030	1.050	100	16.3
NML1-100	1.041	1.066	1.290	1.315	100	25.9
NML1-1/4-50	1.380	1.410	1.635	1.660	50	33.9
NML1-1/2-50	1.575	1.600	1.865	1.900	50	44.6
NML2-50	2.020	2.045	2.340	2.375	50	61.7

All values are nominal and subject to correction.

Application: NMLT is designed for liquid tight applications which are subject to vibration, movement, oil, and corrosives. Suitable for indoor and outdoor use such as indoor lighting, water treatment systems, and HVAC equipment.

Construction: One-piece construction of rigid, non-metallic reinforcement embedded in flexible PVC wall for exceptional crush and corrosion resistance. Durable, sunlight resistant and flame retardant thermoplastic PVC that resists heat, oil and chemical breakdown. Convenient markings in feet for easy measurement.

Standards: UL 1660, listed for direct burial applications
 CSA C22.2 No. 227.2.1
 Sunlight and Oil resistant
 Temperature range: 80°C dry and 60°C wet to -34°C to +70°C

1-877-611-5122